

**Cobra**

**For 135° Corners (+/- 40°)** with PZ/PZC (ball & socket) sheet piles

**Installation**

1. Please review the proper interlocking examples that are listed.
2. Thread the connector into the interlock while the sheet pile is out of the ground.
3. Adjust the connector to the appropriate position.
4. Tack or spot-weld the connector in place. Typically, a ~250mm (~10") weld attaching the connector to the sheet pile to the top is sufficient.
5. Drive/extract the sheet pile (with the connector attached) as you would normally.

**Properties**

Steel grade:	S355GP, S430GP
	ASTM A572 Gr. 50/60
	ASTM A690 MARINER™ Steel
Weight:	~7.44 lb / ft

**Cobra****Raccord à 135°**

Pour PZ- et PZC (Ball + Socket)

**Domaines d'emploi**

Raccordement permettant un angle de 135° (variation possible de +/- 20°)

**Caractéristiques**

Nuances d'acier:	S355GP, S430GP
	ASTM A572 Gr. 50/60
	ASTM A690 MARINER™ Steel
Poids:	~11,1 kg/m

**Cobra****135° Eckverbindung**

Für PZ und PZC (Ball and Socket)

**Einsatzgebiet**

135° Eckverbindungen

**Eigenschaften**

Stahlgüten:	S355GP, S430GP
	ASTM A572 Gr. 50/60
	ASTM A690 MARINER™ Steel
Gewicht:	~11,1 kg/m

**Cobra****Connessione per angolo a 135°**

Per PZ e PZC (maschio e femmina)

**Campo di applicazione**

Connessioni per angolo a 135°

**Caratteristiche**

Qualità dell'acciaio:	S355GP, S430GP
	ASTM A572 Gr. 50/60
	ASTM A690 MARINER™ Steel
Peso:	~11,1 kg/m

**Cobra****Unión angular de 135°**

Para PZ y PZC (Ball and Socket)

**Ámbito de aplicaciones**

Uniones angulares de 135°

**Propiedades**

Calidades de acero:	S355GP, S430GP
	ASTM A572 Gr. 50/60
	ASTM A690 MARINER™ Steel
Peso:	~11,1 kg/m

**Cobra****135° угловой соединительный элемент**

Для PZ и PZC (шар и гнездо)

**Область применения**

Угловые соединительные элементы 135°

**Параметры**

Качество стали:	S355GP, S430GP
	ASTM A572 Gr. 50/60
	ASTM A690 MARINER™ Steel
Вес:	~11,1 кг/м

# Cobra

# for Ball & Socket (PZ / PZC)

